

ATTENTION CUSTOMERS: You will need the liner, front mounting cap and screw from the original forend. This forend requires a metal liner with front mounting screw sleeve for installation; which is not included. The metal liner from the original forend may be used if it is not damaged, deformed or modified in any way. The removal of metal liner from the original forend will require original forend to be split into 2 pieces, making it unusable once completed. Before installing forend liner, ensure all surfaces are free from dried adhesive debris. Rubbing alcohol, or other cleaning agent that will not hinder new adhesive performance, should be used to clean the metal surfaces. Slight fitting may be required to properly fit you specific liner. Make sure the forend retains its intended shape when the liner is installed. Dry fit the metal liner into forend, and onto gun, to ensure proper fit and function. Ensure all inleted surfaces of forend are completely free from debris before applying adhesive. Generously, apply Acraglas adhesive to all inleted surfaces of forend that the liner will make contact with. Also, apply adhesive to metal liner if necessary to ensure proper function of the gun. Once installed make sure to let adhesive dry according to manufactures specifications before use.

ATTENTION CUSTOMERS: You will need the liner, front mounting cap and screw from the original forend. This forend requires a metal liner with front mounting screw sleeve for installation; which is not included. The metal liner from the original forend may be used if it is not damaged, deformed or modified in any way. The removal of metal liner from the original forend will require original forend to be split into 2 pieces, making it unusable once completed. Before installing forend liner, ensure all surfaces are free from dried adhesive debris. Rubbing alcohol, or other cleaning agent that will not hinder new adhesive performance, should be used to clean the metal surfaces. Slight fitting may be required to properly fit you specific liner. Make sure the forend retains its intended shape when the liner is installed. Dry fit the metal liner into forend, and onto gun, to ensure proper fit and function. Ensure all inleted surfaces of forend are completely free from debris before applying adhesive. Generously, apply Acraglas adhesive to all inleted surfaces of forend that the liner will make contact with. Also, apply adhesive to metal liner if necessary to ensure proper function of the gun. Once installed make sure to let adhesive dry according to manufactures specifications before use.